



L'huile des records du monde

LUBE FE - SAE 0W-16

Fuel economy 100% synthetic engine oil

APPLICATIONS

Fully synthetic low viscosity lubricant for gasoline engines and hybrid passenger cars.
LUBE FE 0W16 provides increased fuel economy and keeps CO2 emissions extremely low.

MAIN PHYSICAL DATA

		Units	0W-16
Density at	20° C	kg/m ³	843
Kinematic viscosity at	40° C	mm ² /s	36
Kinematic viscosity at	100° C	mm ² /s	6.9
Viscosity index			155
Flash point Cleveland open cup		°C	225
Pour point		° C	- 39
Dynamic viscosity at	- 35° C	mPa.s	5850

The data given in this table are typical production values and cannot be considered as specifications.

PROPERTIES & ADVANTAGES

- SAE 0W16 very low viscosity provides quick oil flow, increased fuel economy and reduced exhaust gas emissions (CO2, NOx, particulates...), whilst maintaining an excellent engine protection against wear.
- Good detergent/dispersant properties keep engines clean
- Excellent shear stability ensures optimal viscosities at 100 °C and 150 °C for increased lubrication at high temperature.
- Low viscosity at cold temperature for easy start-ups whatever the outside temperature

APPROVALS

API SN

